

Amendment to the Claims

1. (Currently Amended) A transducer comprising:

Sub E 17
a plurality of solid layers, including a magnetically soft loop substantially encircling an electrically conductive coil section and terminating in leading and trailing magnetically soft layers separated by an amagnetic gap layer, said trailing magnetically soft layer being oriented substantially perpendicular to said amagnetic layer, wherein said trailing magnetically soft layer has a width measured in a direction substantially parallel to said amagnetic layer, said width being less than about ~~four~~ two hundred nanometers and greater than about twenty angstroms.

2-11. (Canceled)

12. (Currently Amended) A transducer for an information storage system, the transducer comprising:

D 1
a plurality of solid layers, including a magnetoresistive sensor layer and a magnetically soft loop substantially encircling an electrically conductive coil section and terminating adjacent a media-facing surface in leading and trailing magnetically soft layers separated by an amagnetic gap layer, said trailing magnetically soft layer being oriented substantially perpendicular to said magnetoresistive sensor layer and having a width measured in a direction substantially parallel to said magnetoresistive sensor layer, said width being less than about ~~four~~ two hundred nanometers and greater than about twenty angstroms.

13-81. (Canceled)

82. (Previously Added) The transducer of claim 1, wherein a distance between said magnetically soft layers is not substantially greater than said width.

Sub Ely
cont

83. (Previously Added) The transducer of claim 1, wherein said trailing magnetically soft layer has a length measured in a direction substantially perpendicular to said amagnetic layer, with said length being at least six times greater than said width.

84. (Previously Added) The transducer of claim 1, wherein said trailing magnetically soft layer contains a refractory metal.

85. (Previously Added) The transducer of claim 1, wherein said trailing magnetically soft layer contains material having a B_s higher than that of Permalloy.

86. (Previously Added) The transducer of claim 1, wherein said leading magnetically soft layer is substantially perpendicular to said trailing magnetically soft layer.

D₁
cont

87. (Previously Added) The transducer of claim 1, wherein said trailing magnetically soft layer contains vacuum-deposited material.

88. (Previously Added) The transducer of claim 1, further comprising a magnetoresistive sensor layer disposed adjacent said leading magnetically soft layer and oriented substantially perpendicular to said trailing magnetically soft layer.

89. (Previously Added) The transducer of claim 1, wherein said magnetically soft loop includes a magnetically soft trailing yoke layer that adjoins said trailing magnetically soft layer.

90. (Previously Added) The transducer of claim 89, wherein said trailing yoke layer extends further in said direction substantially parallel to said amagnetic layer than in a direction substantially perpendicular to said amagnetic layer and aligned with said leading and trailing magnetically soft layers.

91. (Previously Added) The transducer of claim 12, wherein said trailing magnetically soft layer is substantially perpendicular to said amagnetic layer.

92. (Previously Added) The transducer of claim 12, wherein said trailing magnetically soft layer is substantially perpendicular to said leading magnetically soft layer.

93. (Previously Added) The transducer of claim 12, wherein said trailing magnetically soft layer has a length measured in a direction substantially perpendicular to said magnetoresistive sensor layer, with said length being at least six times greater than said width.

94. (Previously Added) The transducer of claim 12, wherein said width of said trailing magnetically soft layer is less than about two hundred nanometers.

95. (Previously Added) The transducer of claim 12, wherein said width of said trailing magnetically soft layer is not substantially greater than a thickness of said amagnetic layer.

96. (Previously Added) The transducer of claim 12, wherein said trailing magnetically soft layer contains material having a B_s higher than that of Permalloy.

97. (Previously Added) The transducer of claim 12, wherein said trailing magnetically soft layer contains a refractory metal.

98. (Previously Added) The transducer of claim 12, wherein said trailing magnetically soft layer is sputter-deposited.

99. (Previously Added) The transducer of claim 12, wherein said leading magnetically soft layer is sputter-deposited.

Sub E1
cont

100. (Previously Added) The transducer of claim 12, wherein said magnetically soft loop includes a magnetically soft trailing yoke layer that adjoins said trailing magnetically soft layer.

101. (Previously Added) The transducer of claim 100, wherein said trailing yoke layer extends further in said direction substantially parallel to said magnetoresistive sensor layer than in a direction substantially perpendicular to said magnetoresistive sensor layer and aligned with said leading and trailing magnetically soft layers.

AD
12-28

102-120 (cancelled)

D1
cont

121. (Currently Amended) A transducer comprising:

a magnetoresistive sensor layer,

a magnetically soft loop disposed adjacent to said magnetoresistive sensor layer, traversed by an electrically conductive coil section and including magnetically soft leading and trailing pole-tips disposed adjacent to a media-facing surface, said trailing pole-tip aligned with said magnetoresistive sensor layer along a longitudinal direction and having a width measured in a track-width direction that is perpendicular to said longitudinal direction, said longitudinal and track-width directions being substantially parallel to said media-facing surface, said width being less than ~~four~~ two hundred nanometers and greater than twenty angstroms.

122. (Previously Added) The transducer of claim 121, wherein said trailing pole-tip has a length measured in said longitudinal direction, said length being at least five times greater than said width.

123. (Previously Added) The transducer of claim 121, wherein said leading and trailing pole-tips are separated by a submicron nonferromagnetic gap layer.

124. (Previously Added) The transducer of claim 121, wherein said trailing pole-tip consists essentially of sputtered material.

Sub E1
D1 cond
cont

125. (Previously Added) The transducer of claim 121, wherein said trailing pole-tip contains material having a B_s higher than that of Permalloy.

126. (Previously Added) The transducer of claim 121, wherein said magnetically soft loop includes a magnetically soft yoke layer adjoining said trailing pole-tip.

127. (Previously Added) The transducer of claim 126, wherein said yoke layer extends further in said track-width direction than in said longitudinal direction.

128-134. (Withdrawn)

135-141. (Canceled)
